

MRC

C2-A2x

8-pin standard relay, 2-pole, plug-in according to IEC 67-I-5a

Type	C2-A2x/ ... V Standard relay, 2 change-over contacts		
Maximum contact load	10 A/250 V AC1	0,5 A/110 V DC1	
Recommended minimum contact load	10 A/30 V DC1	0,2 A/220 V DC1	
	1 mA/10 V (with 10 µm Au)		
	10 mA/10 V (Standard contact)		

Contacts			
Material	Standard	Code 0	AgNi
	Optional	Code 8	AgNi + 10 µ Au
	Optional	Code 9	AgNi + 0,2 µ Au
Max. switching current	10 A		
Max. peak inrush current (20 ms.)	30 A		
Max. switching voltage	250 V		
Max. AC load (Table 1)	2,5 kVA		
Max. DC load	See Table 2		

Coils	
Coil resistance	see table; tolerance ± 10 %
Pull-in voltage	≥ 0,8 × U _N
Pull-in voltage	≥ 0,1 × U _N
Nominal power	2,2 VA (AC)/1,3 W (DC)

Table	VAC			VDC		
	VAC	Ω	mA	VDC	Ω	mA
	12	-	-	12	110	110
	24	67	92	24	433	54
	48	296	46	48	1K8	27
	115	1K7	19	110	9K2	12


Insulation	
Open contact	1000 V
Between adjacent poles	2,5 kV
Between contacts and coil	2,5 kV
Insulation resistance at 500 V	≥ 1 GΩ
Insulation, IEC 61810-5	2,5 kV/3

Specifications	
Ambient temperature	-40 (no ice)...60 °C / -40 ... 80 °C
Operate time + bounce time	16 ms/≥ 3 ms
Release time + bounce time	8 ms/≥ 1 ms
Mechanical life ops.	AC: 10 Mill./DC: 20 Mill. relays
AC voltage endurance at rated load	≥ 100000 ops.
Operating frequency at nominal load	≤ 1200/h
Protection degree	IP40
Weight	90 g

Standard types			
AC 50 Hz/60 Hz: 24, 48, 115 (120), 230 (240)	C2-A20/AC ... V	C2-A28/AC ... V	C2-A29AC ... V
LED	C2-A20X/AC ... V	C2-A28X/AC ... V	C2-A29X/AC ... V
RC Suppressor	C2-A20R/AC ... V	C2-A28R/AC ... V	C2-A29R/AC ... V
DC 24, 48, 110, 220	C2-A20/DC ... V	C2-A28/DC ... V	C2-A29/DC ... V
LED	C2-A20X/DC ... V	C2-A28X/DC ... V	C2-A29X/DC ... V
Free wheeling diode	C2-A20DX/DC ... V	C2-A28DX/DC ... V	C2-A29DX/DC ... V
V Polarity and free wheeling diode	C2-A20FX/DC ... V	C2-A28FX/DC ... V	C2-A29FX/DC ... V
AC/DC bridge rectifier 24 V, 48 V, 60 V	C2-A20BX/UC ... V	C2-A28BX/UC ... V	C2-A29BX/UC ... V

"..." Relay compatible with sockets S2-B, S2-S, S2-L and S2-PO

Relay compatible with sockets **S2-B, S2-S, S2-L, S2-P, S2-PO**
SO-NP, SO-OP



Connection diagram




Fig. 1 AC voltage endurance







Fig. 2 DC load limit curve



Dimensions [mm]



Technical approvals, conformities





Kühn Controls AG

Notes:

You want more information about this product, please call us: tel: +49 (0)7082-940000 or send us a fax: +49 (0)7082-940001, or email: sales@kuehn-controls.de or visit our Website: www.kuehn-controls.de