

TECHNICAL OFFER

16/05/2018

Customer name	Wouter Witzel Eurovalve BV	Quotation	QTB007045-1
Contact	Dhr. Michel van der Leest	Line no.	1
Customer reference	Q18068	Expiry date	14/08/2018
		Transmitter	Valerie VOLS
		Delivery time	8 semaines/weken

SERVICE CONDITIONS			
SERVICE CONDITIONS	Required torque O (Nm) ..: 120	Stem diam. (mm)	0.00
	Required torque C (Nm) ..: 120	VALVE Lead (mm)	0.00
	Number of turns in output ..: 0.25	Lift (mm)	0.00
Closing direction	Clockwise	Fail safe function	Valve closed
Customer specifications			
Observation			

ACTUATOR	
Actuator	FQ12
Actuator's speed (Rpm)	0.16

MECHANICAL SPECIFICATIONS	
Protection	_NotExplosionProof IP67
Box type	Standard
Class	A
Output speed (RPM)	0.16
Operating time (s)	93
Max torque (Nm)	120
Torque set O (Nm)	120
Torque set C (Nm)	120
Temperature	Standard -20°C to 70°C
Output flange	F10
Output form	N/A
Machining type	□
Manual command	Declutchable Ø 160 mm
Paint	BCPS-C3-01
Painting process	Intermediate Corrosi
Color	RAL 5002 MARINE BLUE
Spring return time (sec)	10

MOTOR SPECIFICATIONS				
Motor	Electric 1Ph 230V 50Hz	Motor duty (%)	S4 - 30	
Power (kW)	0.030	Nominal intensity (A) : 0.50	Starting current (A)	1.10

ELECTRICAL SPECIFICATIONS	
Control type	Switch
Options (incl.)	
End of travel limit switches ...:	Opening : 2 & Closing : 2 - Type : SPDT
Torque limit switches qty	Opening : 1 & Closing : 1 - Type : SPDT
Customer's connection	Plug plastic 2xM20 ISO
Heater	230 V 25 W
Brake supply	1Ph 230V 50Hz

PARTICULAR SPECIFICATIONS			
Quality level	Q3	Quality plan	
Electronic card's configure:	Standard	Dimensional drawing ...:	z251000 Ver. A
		Orientations :	